

*NEW &
IMPROVED*



6800 SERIES RIPPER-BEDDER



*THE KEY TO A SUPERIOR
BEDDING JOB EVERY TIME!*

- IMPROVED MOISTURE MANAGEMENT
- FASTER SOIL WARM UP FOR EARLIER PLANTING
- IN-ROW SUBSOILING FOR DEEPING ROOT PENETRATION, HEALTHIER PLANTS
- UNIFORM, PEAK SEEDBEDS

THE 6800 SERIES RIPPER-BEDDER HAS BEEN DESIGNED WITH DURABILITY TO HANDLE TOUGH BEDDING OPERATIONS IN LIGHT OR HEAVY SOIL TYPES, WHILE DELIVERING A QUALITY BEDDING JOB. AVAILABLE IN THE WIDEST RANGE OF MODELS AND SIZES ANYWHERE, ALL RIPPER-BEDDER MODELS (AND SOME CONVENTIONAL DISC BEDDER MODELS) ARE EQUIPPED WITH A 7X7 HEAVY DUTY, ALL WELDED, DOUBLE-FRAME TOOLBAR.

KEY FEATURES

- ON ROW RIPPER SHANKS ATTACHED TO MAIN 7X7 TOOLBAR
- DOUBLE (18" AND 20" DIA.) OR SINGLE (20" DIA.) DISC GANGS WITH CAST IRON HUBS AND TRIPLE SEALED BEARINGS
- PARALLEL LINKAGES CONNECTING FRONT MAIN TOOLBAR WITH REAR TOOLBAR PERMIT DISC GANGS TO FLOAT INDEPENDENT OF RIPPER SHANKS
- 8" X 10" ADJUSTABLE GAUGE WHEELS ON REAR TOOLBAR PROVIDE FLOTATION FOR UNIFORM BED HEIGHTS
- PARKING STANDS
- ONE PAIR SCREW TYPE ADJUSTABLE GAUGE WHEELS ARE STANDARD EQUIPMENT ON 6 AND 8 ROW MODELS. TWO PAIR GAUGE WHEELS ARE STANDARD EQUIPMENT ON 12 AND 16 ROW MODELS. 12 AND 16 ROW MODELS MAY REQUIRE ADDITIONAL GAUGE WHEELS DEPENDING ON SOIL CONDITIONS.



WHAT'S NEW

- PATENT PENDING RESET ON THE GO SHANK ALLOWS FOR CONTINUOUS OPERATION WITHOUT LIFTING IMPLEMENT
- MADE OF HIGH STRENGTH, ABRASION RESISTANT STEEL
- WEAR SHIN PROTECTED WITH 6000 POUNDS TRIP FORCE
- BREAK HARDPAN UP TO 20" DEEP





AVAILABLE OPTIONS

- **BED SHAPER KITS**
- **ROW MARKERS**
- **DISC SCRAPERS**
- **BALK PLOWS**
- **TRACTOR LIFT HELPER WHEELS**



SPECIFICATIONS

KMC

KELLEY

KELLEY MANUFACTURING CO.
P.O. Box 1467 TIFTON, GEORGIA 31793
WWW.KELLEYMFG.COM
1-800-444-5449



Rigid	Transport Width	Approximate Weight	Hitch Type
4 Row 36"	161"	3,873 lb	CAT II-3PT, CAT II-QC, CAT III-3PT, CAT III-QC, CAT III-NQC
4 Row 38"	161"	3,873 lb	CAT II-3PT, CAT II-QC, CAT III-3PT, CAT III-QC, CAT III-NQC
4 Row 40"	161"	3,873 lb	CAT II-3PT, CAT II-QC, CAT III-3PT, CAT III-QC, CAT III-NQC
4 Row 46"	200"	4,200 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
4 Row 48"	200"	4,200 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
6 Row 30"	183"	4,959 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
6 Row 36"	229"	5,547 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
6 Row 38"	229"	5,547 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
6 Row 40"	251"	5,662 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
8 Row 30"	251"	6,466 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
Stack Fold			
8 Row 36"	162"	8,804 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
8 Row 38"	162"	8,813 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
8 Row 40"	162"	8,813 lb	CAT III-3PT, CAT III-QC, CAT III-NQC
8 Row 46"	230"	9,544 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
8 Row 48"	240"	9,544 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
12 Row 30"	220"	12,019 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
12 Row 36"	242"	12,671 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
12 Row 38"	242"	12,671 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
12 Row 40"	288"	13,016 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC
16 Row 30"	288"	14,489 lb	CAT III-3PT, CAT III-QC, CAT III-NQC, CAT IV-NQC

- RECOMMENDED HORSEPOWER REQUIREMENTS: 25-30 HP PER SHANK
- TOOLBARS: 4"X7" FRONT HITCH BAR, 7"X7" MAIN TOOLBAR
- 4"X4" REAR TOOLBAR

